



600 Kw Cummins 3 Phase Diesel Generator 50HZ 60HZ With Water Cooling System

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT-Cummins
- Certification: CE/ISO9001
- Model Number: DE-CC825
- Minimum Order Quantity: 1 PC
- Price: bargain face-to-face
- Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
- Delivery Time: 20-30 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 1 MONTH 600PCS



Product Specification

- Name: Cummins 3 Phase Diesel Generator
- Engine Brand: Cummins
- Cooling Method: Water-Cooling System
- Fuel Type: Diesel
- Rated Frequency: 50HZ/60HZ
- Speed: 1500RPM/1800RPM
- Warranty: 12 Months/1000 Hours
- Highlight: **Cummins 3 Phase Diesel Generator 50HZ,
CE Cummins 3 Phase Diesel Generator,
600 Kw Cummins Generator**

for more products please visit us on dellentpower.com

CE Cummins Diesel Generator about 600kW.

As an authorized Cummins generator dealer, we offer a wide range of models to suit any power needs and budget. From compact and portable generators to heavy-duty industrial generators, we have the expertise and resources to help you find the perfect generator for your needs.

At our Cummins generator dealership, we understand the importance of quality and reliability when it comes to power generation. That's why we only offer the best generators from Cummins , a leading manufacturer of power equipment.

. PRODUCT

50-000 TECHNICAL DATA

General Information			Engine Performance			Generator Data		
Model	Power (kW)	Power (kVA)	Engine (kW)	Engine (kVA)	Generator (kW)	Generator (kVA)	Rated Voltage (V)	Rated Frequency (Hz)
50-0225	25	33.3	25	33.3	25	33.3	400	50
50-0230	30	39.6	30	39.6	30	39.6	400	50
50-0235	35	45.9	35	45.9	35	45.9	400	50
50-0240	40	52.2	40	52.2	40	52.2	400	50
50-0245	45	58.5	45	58.5	45	58.5	400	50
50-0250	50	64.8	50	64.8	50	64.8	400	50
50-0255	55	71.1	55	71.1	55	71.1	400	50
50-0260	60	77.4	60	77.4	60	77.4	400	50
50-0265	65	83.7	65	83.7	65	83.7	400	50
50-0270	70	90.0	70	90.0	70	90.0	400	50
50-0275	75	96.3	75	96.3	75	96.3	400	50
50-0280	80	102.6	80	102.6	80	102.6	400	50
50-0285	85	108.9	85	108.9	85	108.9	400	50
50-0290	90	115.2	90	115.2	90	115.2	400	50
50-0295	95	121.5	95	121.5	95	121.5	400	50
50-0300	100	127.8	100	127.8	100	127.8	400	50
50-0305	105	134.1	105	134.1	105	134.1	400	50
50-0310	110	140.4	110	140.4	110	140.4	400	50
50-0315	115	146.7	115	146.7	115	146.7	400	50
50-0320	120	153.0	120	153.0	120	153.0	400	50
50-0325	125	159.3	125	159.3	125	159.3	400	50
50-0330	130	165.6	130	165.6	130	165.6	400	50
50-0335	135	171.9	135	171.9	135	171.9	400	50
50-0340	140	178.2	140	178.2	140	178.2	400	50
50-0345	145	184.5	145	184.5	145	184.5	400	50
50-0350	150	190.8	150	190.8	150	190.8	400	50
50-0355	155	197.1	155	197.1	155	197.1	400	50
50-0360	160	203.4	160	203.4	160	203.4	400	50
50-0365	165	209.7	165	209.7	165	209.7	400	50
50-0370	170	216.0	170	216.0	170	216.0	400	50
50-0375	175	222.3	175	222.3	175	222.3	400	50
50-0380	180	228.6	180	228.6	180	228.6	400	50
50-0385	185	234.9	185	234.9	185	234.9	400	50
50-0390	190	241.2	190	241.2	190	241.2	400	50
50-0395	195	247.5	195	247.5	195	247.5	400	50
50-0400	200	253.8	200	253.8	200	253.8	400	50
50-0405	205	260.1	205	260.1	205	260.1	400	50
50-0410	210	266.4	210	266.4	210	266.4	400	50
50-0415	215	272.7	215	272.7	215	272.7	400	50
50-0420	220	279.0	220	279.0	220	279.0	400	50
50-0425	225	285.3	225	285.3	225	285.3	400	50
50-0430	230	291.6	230	291.6	230	291.6	400	50
50-0435	235	297.9	235	297.9	235	297.9	400	50
50-0440	240	304.2	240	304.2	240	304.2	400	50
50-0445	245	310.5	245	310.5	245	310.5	400	50
50-0450	250	316.8	250	316.8	250	316.8	400	50
50-0455	255	323.1	255	323.1	255	323.1	400	50
50-0460	260	329.4	260	329.4	260	329.4	400	50
50-0465	265	335.7	265	335.7	265	335.7	400	50
50-0470	270	342.0	270	342.0	270	342.0	400	50
50-0475	275	348.3	275	348.3	275	348.3	400	50
50-0480	280	354.6	280	354.6	280	354.6	400	50
50-0485	285	360.9	285	360.9	285	360.9	400	50
50-0490	290	367.2	290	367.2	290	367.2	400	50
50-0495	295	373.5	295	373.5	295	373.5	400	50
50-0500	300	379.8	300	379.8	300	379.8	400	50
50-0505	305	386.1	305	386.1	305	386.1	400	50
50-0510	310	392.4	310	392.4	310	392.4	400	50
50-0515	315	398.7	315	398.7	315	398.7	400	50
50-0520	320	405.0	320	405.0	320	405.0	400	50
50-0525	325	411.3	325	411.3	325	411.3	400	50
50-0530	330	417.6	330	417.6	330	417.6	400	50
50-0535	335	423.9	335	423.9	335	423.9	400	50
50-0540	340	430.2	340	430.2	340	430.2	400	50
50-0545	345	436.5	345	436.5	345	436.5	400	50
50-0550	350	442.8	350	442.8	350	442.8	400	50
50-0555	355	449.1	355	449.1	355	449.1	400	50
50-0560	360	455.4	360	455.4	360	455.4	400	50
50-0565	365	461.7	365	461.7	365	461.7	400	50
50-0570	370	468.0	370	468.0	370	468.0	400	50
50-0575	375	474.3	375	474.3	375	474.3	400	50
50-0580	380	480.6	380	480.6	380	480.6	400	50
50-0585	385	486.9	385	486.9	385	486.9	400	50
50-0590	390	493.2	390	493.2	390	493.2	400	50
50-0595	395	499.5	395	499.5	395	499.5	400	50
50-0600	400	505.8	400	505.8	400	505.8	400	50
50-0605	405	512.1	405	512.1	405	512.1	400	50
50-0610	410	518.4	410	518.4	410	518.4	400	50
50-0615	415	524.7	415	524.7	415	524.7	400	50
50-0620	420	531.0	420	531.0	420	531.0	400	50
50-0625	425	537.3	425	537.3	425	537.3	400	50
50-0630	430	543.6	430	543.6	430	543.6	400	50
50-0635	435	549.9	435	549.9	435	549.9	400	50
50-0640	440	556.2	440	556.2	440	556.2	400	50
50-0645	445	562.5	445	562.5	445	562.5	400	50
50-0650	450	568.8	450	568.8	450	568.8	400	50
50-0655	455	575.1	455	575.1	455	575.1	400	50
50-0660	460	581.4	460	581.4	460	581.4	400	50
50-0665	465	587.7	465	587.7	465	587.7	400	50
50-0670	470	594.0	470	594.0	470	594.0	400	50
50-0675	475	600.3	475	600.3	475	600.3	400	50
50-0680	480	606.6	480	606.6	480	606.6	400	50
50-0685	485	612.9	485	612.9	485	612.9	400	50
50-0690	490	619.2	490	619.2	490	619.2	400	50
50-0695	495	625.5	495	625.5	495	625.5	400	50
50-0700	500	631.8	500	631.8	500	631.8	400	50
50-0705	505	638.1	505	638.1	505	638.1	400	50
50-0710	510	644.4	510	644.4	510	644.4	400	50
50-0715	515	650.7	515	650.7	515	650.7	400	50
50-0720	520	657.0	520	657.0	520	657.0	400	50
50-0725	525	663.3	525	663.3	525	663.3	400	50
50-0730	530	669.6	530	669.6	530	669.6	400	50
50-0735	535	675.9	535	675.9	535	675.9	400	50
50-0740	540	682.2	540	682.2	540	682.2	400	50
50-0745	545	688.5	545	688.5	545	688.5	400	50
50-0750	550	694.8	550	694.8	550	694.8	400	50
50-0755	555	701.1	555	701.1	555	701.1	400	50
50-0760	560	707.4	560	707.4	560	707.4	400	50
50-0765	565	713.7	565	713.7	565	713.7	400	50
50-0770	570	720.0	570	720.0	570	720.0	400	50
50-0775	575	726.3	575	726.3	575	726.3	400	50
50-0780	580	732.6	580	732.6	580	732.6	400	50
50-0785	585	738.9	585	738.9	585	738.9	400	50
50-0790	590	745.2	590	745.2	590	745.2	400	50
50-0795	595	751.5	595	751.5	595	751.5	400	50
50-0800	600	757.8	600	757.8	600	757.8	400	50
50-0805	605	764.1	605	764.1	605	764.1	400	50
50-0810	610	770.4	610	770.4	610	770.4	400	50
50-0815	615	776.7	615	776.7	615	776.7	400	50
50-0820	620	783.0	620	783.0	620	783.0	400	50
50-0825	625	789.3	625	789.3	625	789.3	400	50
50-0830	630	795.6	630	795.6	630	795.6	400	50
50-0835	635	801.9	635	801.9	635	801.9	400	50
50-0840	640	808.2	640	808.2	640	808.2	400	50
50-0845	645	814.5	645	814.5	645	814.5	400	50
50-0850	650	820.8	650	820.8	650	820.8	400	50
50-0855	655	827.1	655	827.1	655	827.1	400	50
50-0860	660	833.4	660	833.4	660	833.4	400	50
50-0865	665	839.7	665	839.7	665	839.7	400	50
50-0870	670	846.0	670	846.0	670	846.0	400	50
50-0875	675	852.3	675	852.3	675	852.3	400	50
50-0880	680	858.6	680	858.6	680	858.6	400	50
50-0885	685	864.9	685	864.9	685	864.9	400	50
50-0890	690	871.2	690	871.2	690	871.2	400	50
50-0895	695	877.5	695	877.5	695	877.5	400	50
50-0900	700	883.8						



. FACTORY INTERIOR:



Fuan Dellent Electric & Machinery Co., Ltd.



+8613706938606



jennifer@dellent.com



dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN
CITY,NINGDE CITY,FUJIAN.CHINA